


Temperature Humidity Sensor

6834



The Davis Temperature Humidity Sensor is unshielded and meant for indoor use. It includes both sensors in a small, mountable housing. To transmit the data to a console or WeatherLink Live, use an AC-Powered Sensor Transmitter, product number 6331.

General

Operating Temperature	-40° to +150° F (-40° to +65° C)
Housing Material	UV-resistant PVC plastic
Dimensions	1.5" H X 2.6" L X 1.4 D (38 mm x 66 mm x 36 mm)
Weight	8 oz (0.23 kg)
Cable Length	25 feet (7.6 meters)
Humidity	
Resolution and Units	1% (console); 0.1% WeatherLink Live
Range	1 to 100% RH
Accuracy	±2%
Drift	<0.25% per year
Update Interval	50 seconds to 1 minute
Temperature	
Resolution and Units	Current Data: 1°F or 1°C (user-selectable) °C is converted from °F rounded to the nearest 1°C Historical Data and Alarms: 1°F or 1°C (user-selectable)
Range	-40° to +150°F (-40° to +65°C)
Sensor Accuracy	±0.5°F (±0.3°C)
Update Interval	0 to 12 seconds

Package Dimensions

Product #	Package Dimensions (Length x Width x Height)	Package Weight	UPC Codes
6834	6.5" x 3" x 2.3" (165 mm x 76 mm x 58 mm)	10.2 ounces (0.3 kg)	011698013746